



***GAS*pipe**

Rúry a tvarovky



www.gaspipe.sk

gaspipe@gaspipe.sk

Pipes and fittings

Spoločnosť GASPIPE s. r. o. vznikla dňa 08.08.2009 ako obchodná spoločnosť špecializovaná na predaj oceľových rúr, tvaroviek a ostatného príslušenstva pre plyn, vodu, kanalizáciu a kúrenie.

Ponúkame svoje služby nielen stavebným spoločnostiam, ale aj drobným montážnym firmám a iným obchodným spoločnostiam na celom území Slovenska i v zahraničí. Tieto produkty sú dodávané podľa noriem ČSN, DIN, EN, ASTM, GOST, NFA, API

Cieľom spoločnosti je dodávať zákazníkom vysoko kvalitný a cenovo prístupný sortiment v čo najkratšom časovom termíne.

Company GASPIPE s.r.o. was established in 08.08.2009 as a trading company specialized in selling steel tubes, fittings and other accessories for gas, water, sewerage and heating.

Company offers his service not only to building companies, but also to small installing companies and other trading companies in the territory of Slovak Republic and abroad. We deliver these products acc. to standards ČSN, DIN, EN, ASTM, GOST, NFA, API.

The main priority of company is to deliver high quality and price accessible assortment in the shortest time.

***GAS*pipe**

GASPIPE s.r.o., Novozámocká 180, 947 03 Hurbanovo – Bohatá, Slovakia

Tel.: +421 (35) 761 1080, Fax: +421 (35) 761 0069



Oceľové rúry / Steel pipes

Druh rúry Type of pipe	Pozdĺžne zvárané rúry HFI pipes	Pozdĺžne zvárané rúry LSAW pipes	Špirálovo zvárané rúry SAWH welded pipes	Bezošvé rúry Seamless pipes
Normy / Akost' Standards/ Material	DIN 1626, DIN 1629 DIN 1628 EN 10208 – 1 EN 10208 – 2 API 5L -	St 37.0, St 44.0 ,St 52.0 St 37.4,St 44.4, St 52.4 L 210 GA ,L 235 GA,L 245 GA, L 290 GA ,L 360 GA L 245 NB ,L 290 NB,L 360 NB, L 415 NB/MB,L 450 MB,L 485 MB,L 555 MB Grad A 25,B,X 42,X 46,X 52,X 56,X 60,X 65,X 70,X 80, X 100		
Rozmery / Dimensions	33,7 – 610,0 mm	406,4 – 2540 mm	323,0 – 2540 mm	17,1 – 711,0 mm
Hrúbka steny Wall thicknesses	3,2 – 20,6 mm	6,4 – 76,2 mm	5,0 – 21,0 mm	2,3 – 102,0 mm
Vyhotovenie Versions	Čierne bez izolácie / Black without coating PE – izoláciou podľa DIN 30670 / PE coating acc. to DIN 30670 PP - izolácia podľa DIN 30678 / PP coating acc. to DIN 30678 FCM-S – izolácia podľa DVWG -GW 340 / FCM-S – coating acc. to DVWG -GW 340 Vnútoraná cementová izolácia podľa DIN 2880 / cement mortar linings acc. to DIN 2880			



Sklolaminátové rúry a tvarovky / FiberGlass pipes and fittings

Druh rúry Type of pipe	Advance Composite Thread (ACT)	Precision Ground Thread (PGT)	STAR™ Super Seal High Pressure (SSSHP)	STAR™ Super Seal (SSS)	Red Thread® II	Red Thread® II Performance Plus
Rozmery Dimensions	1 ½" - 8"	2" – 8"	1 ½" - 6"	2" – 12"	2" – 24"	8" – 24"
Statický tlak Static pressure	500 – 4000 psi 3,4 – 27,6 MPa	500 – 3000 psi 3,4 – 20,7 Mpa	500 – 2500 psi 3,4 – 17,2 Mpa	500 – 1250 psi 3,4 – 8,6 MPa	225 – 450 psi 1,6 – 3,2 MPa	450 Psi 3,2 MPa
Systém živice Resin System	Anhydride Aliphatic Amine Aromatic Amine	Anhydride Aliphatic Amine Aromatic Amine	Anhydride	Aliphatic Amine	Aromatic Amine	Aromatic Amine
Max. teplota (°C) Max. temp. (°F)	150 °F (65,6°C) 200 °F (93,3°C) 220 °F (104,4°C)	150 °F (65,6°C) 200 °F (93,3°C) 220 °F (104,4°C)	150 °F (65,6°C)	200 °F (93,3°C)	210 °F (98,9°C)	200 °F (93,3°C)
Tvarovky Fittings	Kolená, T- kusy, redukcie, objímky, vsuvky, prechodky, príruby a iné Elbows, tees, reducers, bushing, nipples, crossovers, flanges tec.					



Oceľové tvarovky / Steel Fittings

Druh tvarovky Type of fittings	Kolená / Elbows	T-kusy / T-pieces	Dná / caps	Redukcie / Reducers	Ohyby / Bends
Rozmery / Dimensions	1" – 102"	1" – 102"	1" – 102"	1" – 102"	1" – 64"
Normy / Standards Akost' / materiál	ASTM/ASME A/SA234	WPB, WPC, WP1, WP11, WP12, WP5, WP22, WP9, WP91			Rúrový materiál Pipe material
	EN 10216-2	P195GH, P235GH, P265GH, 20MnNb6,16Mo3 8MoB5-4,14MoV63,10CrMo5-5,13CrMo4-5,10CrMo9-10 15NiCuMoNb5-6-4, X11CrMo5 X,11CrMo9-1, X10CrMoVNB9-1 X10CrWMoVNB9-2, X20CrMoV11-1			
	ASTM A860/ MSS SP-75	WPHY 42, WPHY 46, WPHY 52, WPHY60, WPHY 65 WPHY 70 grades			
	EN 10208-2	L245NB, L290NB, L360NB, L415NB, L360QB, L415QB, L450QB L485QB, L555QB			
	EN 10208-2	L245NB, L290NB, L360NB, L415NB, L360QB, L415QB, L450QB L485QB, L555QB			
	ASTM/ASME A/SA 420	WPL6, WPL3			
Výrobné normy Manufacturing standards	ASME B16.9 - B16.28 - B16.25				
	DIN 2605 - 2606 - 2615 - 2616 – 2617				
	MSS-SP75 – 43				

Spoločnosť GASPIPE s.r.o. disponuje skladovými zásobami a vlastnou nákladnou dopravou.
Company GASPIPE s.r.o. has its own stock and own freight traffic.

